

Recycled Content of Atlas Polyisocyanurate

ISSUED:	10/13/2003
*UPDATED:	08/01/2024
PAGES:	01

³SUPERSEDES EXISTING DOCUMENTS

PRODUCT	THICKNESS							
	0.5"	1.0"	1.5"	2.0"	2.5"	3.0"	3.5"	4.0"
¹ ACFoam®-II	-	52.9%	44.6%	39.2%	35.5%	32.7%	30.6%	28.9%
² ACFoam®-III	-	6.2%	7.7%	8.7%	9.4%	10.0%	10.5%	10.9%
² ACFoam®-HD CoverBoard	7.4%	-	-	-	-	-	-	-
² ACFoam®-Recover Board	3.9%	6.2%	-	-	-	-	-	-
² ACFoam® Supreme	-	11.5%	12.3%	12.8%	13.1%	13.3%	13.5%	13.6%
² EnergyShield®	9.5%	11.5%	12.3%	12.8%	13.1%	13.3%	13.5%	13.6%
² EnergyShield® CGF	3.9%	6.2%	7.7%	8.7%	9.4%	10.0%	10.5%	10.9%
² EnergyShield® CGF Pro	4.6%	7.0%	8.4%	9.4%	10.1%	10.6%	11.1%	11.4%
² EnergyShield® PanelCast	3.9%	6.2%	7.7%	8.7%	9.4%	10.0%	10.5%	10.9%
² EnergyShield® Pro	9.2%	11.2%	12.1%	12.7%	13.0%	13.2%	13.4%	13.5%
² EnergyShield® XR	9.5%	11.5%	12.3%	12.8%	13.1%	13.3%	13.5%	13.6%

¹Post-Consumer and Pre-Consumer (Post-Industrial) recycled content.

²Pre-Consumer (Post-Industrial) recycled content only.

Recycled content values have been established as a percentage of product weight. Download the applicable Package and Loading Guide at www.atlasrwi.com for an extended list of available ACFoam® and EnergyShield® product information.